



VMC
 Vertikální
 obráběcí
 centra



NXV Series

| Typ stroje | NXV560A | NXV560A-APC | NXV1020A | NXV1020AM | NXV1380A | NXV1680A | NXV1680B |
|----------------------------|--|------------------|----------------|----------------|---|----------------|------------------------------|
| Velikost stolu | 700 x 420 mm | 560 x 410 mm * 2 | 1.120 x 520 mm | | 1.430 x 760 mm | 1.730 x 760 mm | 1.730 x 860 mm |
| Pojezd v ose X | 560 mm | | 1.020 mm | | 1.330 mm | 1.630 mm | 1.630 mm |
| Pojezd v ose Y | 410 mm | | 520 mm | | 762 mm | 762 mm | 860 mm |
| Pojezd v ose Z | 450 mm | | 540 mm | | 700 mm | 700 mm | 762 mm |
| Rychloposuvy v osách X/Y/Z | 48/48/48 m/min | | 48/48/32 m/min | 24/24/16 m/min | 30/30/24 m/min | | 24/24/24 m/min |
| Otáčky vřetene | 12.000 ot/min (15.000 ot/min) | | | | 12.000 ot/min (12.000 ot/min/15.000 ot/min) | | 6.000 ot/min (10.000 ot/min) |
| Výkon vřetenového motoru | 18,5 kW (18,5 kW) | | | | 18,5 kW (30 kW/18,5 kW/30 kW) | | 18,5 kW (22 kW) |
| Kužel vřetene | BBT40/ISO40 | | | | | | BT50/BBT50/ISO50 |
| Zásobník nástrojů | 20 ks (24 ks) | | 24 ks (30 ks) | | | | 32 ks (40 ks) |
| Hmotnost stroje | 3.000 kg | 3.830 kg | 5.350 kg | | 10.500 kg | 11.000 kg | 15.500 kg |
| Řídicí systém | Fanuc MXP-200FA (Heidenhain iTNC 530/Siemens 828D) | | | | | | |